

(19) World Intellectual Property  
Organization  
International Bureau



04 OCT 2004

(43) International Publication Date  
5 August 2004 (05.08.2004)


PCT

(10) International Publication Number  
**WO 2004/065146 A1**

- (51) International Patent Classification<sup>7</sup>: **B60G 7/00**
- (21) International Application Number:  
PCT/CA2004/000055
- (22) International Filing Date: 15 January 2004 (15.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2,416,703 20 January 2003 (20.01.2003) CA
- (71) Applicant (for all designated States except US): **MULTI-MATIC INC.** [CA/CA]; 85 Valleywood Drive, Markham, Ontario L3R 5E5 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HOWELL, Robert, Alexander** [CA/CA]; 27 Dopp Cres., Brooklin, Ontario L2M 2E5 (CA). **GRUBER, Rudolf** [AT/CA]; 12 Hillborne Ct, R.R. #4, Uxbridge, Ontario L9P 1R4 (CA).
- (74) Agent: **ZIMMERMAN, Gordon**; Borden Lardner Gervais LLP, 40 King Street West, Scotia Plaza, Toronto, Ontario M5H 3Y4 (CA).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: **STRUCTURAL I-BEAM AUTOMOTIVE SUSPENSION ARM**



(57) Abstract: A vehicular suspension arm (10) comprises an upper sheet metal stamped component (11) with a first outer face and a first inner face (19), and a first central web portion (17) with two opposites sides and first upstanding flange portions (13) at opposites sides of the first web portion, a lower sheet metal stamped component (12) with a second outer face and a second inner face (19), and a second central web portion (17) with two opposite sides and a second upstanding flange portions (13) at the opposite sides of the second web portion, the first and second inner faces (19) adapted to contact each other along a substantial portion of the first and second web portions (17), the upper and lower stamped components (11, 12) adapted to be rigidly attached to each other to create a structural I-beam section, wherein the thickness of each upstanding flange portion (13) is at least equal to the combined thickness of the first and second web portions (17).